carrier signals includes modulating an information signal onto the carrier signals.

93. A spread-spectrum signal generator comprising a multicarrier generator (14n) capable of generating a plurality of electromagnetic carrier signals having a plurality of frequencies, the improvement comprising:

a delay controller (16n) capable of applying a plurality of incremental phase offsets to the carrier signals for providing the carrier signals with a predetermined phase space at a predetermined time interval,

a gain controller (I8n) capable of providing a predetermined gain profile to the carrier signals, and

a combiner (20) capable of combining the modulated, phased carriers to produce a spread spectrum signal from at least one superposition of the carrier signals.

94. The spread-spectrum signal generator claimed in Claim 93 wherein the delay controller (16n) and the gain controller (18n) provide phase offsets and a gain profile, respectively, that provides the superposition of the carrier signals with a direct-sequence spread-spectrum signal.

REMARKS

Newly presented claims 44-94 contain 51 total claims, of which 7 claims are independent claims. Newly presented claim 44 is based upon cancelled claim 1, which is believed to address issues raised in the International Preliminary Examination Report.

Respectfully submitted,

August 9, 2000

Carol W. Burton Reg. No. 35,465

HOGAN & HARTSON LLP 1200 17th Street, Suite 1500

Denver, CO 80202

Telephone (303) 454-2454 Facsimile (303) 899-7333